



A NEW POINT OF VIEW

2000 & 5100 Contractor Series

OVERALL FEATURES

- 3-1/4" frame depth for traditional pocket window installation. Flange and fin options available on double hung and sliding windows to meet a variety of installation options (flange, no fin or nail fin with J-channel)
- Hidden SilLock design with a sloped sill eliminates the need for weep holes, forces water to drain to the exterior of the window and keeps your windows dry, providing enhanced weather-tight performance
- 7/8" IGU glass systems with energy efficient Warm Edge (standard) or Warm Edge+ (optional upgrade) available in Low-E, HP or HP_{MAX} glass package options
- All product styles can be configured to meet ENERGY STAR® requirements in all states
- **NEW** The Energy Package Upgrade options include any glass package option with the addition of R-Core® insulation to the sash and frame for unsurpassed energy efficiency
- NFRC rated and certified



Shown in Contractor 2000 Series Double Hung corner cut featuring HP_{MAX} glass package upgrade with High DP Performance option

Color Options

EXTERIOR & INTERIOR COLOR OPTIONS



NEW!

PAINTED EXTERIOR COLOR OPTIONS WITH WHITE INTERIOR



Warm Edge Spacer reduces thermal transfer around the glass perimeter to interrupt the natural flow of heat to cold



NEW!

R-Core® insulated frame and sash available with Energy Package option



2000 Double Hung Window

FEATURES


- Designed with equal sight line sash for traditional wood window appearance
- Both sash tilt in and are removable for easy and safe cleaning
- Integral interlock system provides protection against air infiltration and makes window more secure
- Double weatherstripped sash provides extra protection against dust, dirt and noise
- High DP performance option, featuring reinforced sash, ensures security and peace of mind in threatening weather
- Interior and exterior accessory grooves allows for a wide selection of installation options
- Locking pivot bar and shoe assembly in upper sash and jamb jacks at meeting rail help ensure a square installation and enhance energy efficiency
- Two ventilation limit latches standard, child safety latches optional
- Extruded aluminum half screen with fiberglass mesh standard; full screen optional



2000 Sliding Window

FEATURES

- Convenient lift-out sash for easy cleaning
- Track and adjustable roller system for ease of operation
- Double-opposed weatherstrip on sash ensures smooth operation
- High DP performance option, featuring reinforced sash, ensures security and peace of mind in threatening weather
- One ventilation limit latch standard or child safety latch optional at bottom rail
- Interior and exterior accessory grooves allows for a wide selection of installation options
- Extruded aluminum half screen with fiberglass mesh



High DP Performance option features reinforced meeting rails



High DP Performance option features reinforced rails and stiles

Images show metal reinforcement in a double hung configuration. Also available for a sliding window.

5100 Casement & Awning

FEATURES

- Interior and exterior accessory grooves allows for a wide selection of installation options
- Available right- or left-hand operating
- Sash opens 90° for ventilation and easy cleaning
- Single-handle multi-point locking system
- Awning windows can be combined / mulled / stacked with fixed casement picture windows
- Adjustable hinges
- Full screen with fiberglass mesh



Color-coordinated lock features a sleek low profile that won't interfere with window dressing



Color-coordinated crank handle



Split-arm gear operator on sizes up to 36" x 60". Dual-arm gear operator on larger units

For more information, call **888-9PLYGEM**
or visit plygem.com/windows



ENERGY STAR® is a registered trademark of the U.S. Environmental Protection Agency. © 2020 Ply Gem Windows & Doors, part of the Cornerstone Building Brands family. ALL RIGHTS RESERVED.
3710207221101/MS/CG/1020