



## 200 Single Hung

**Style. Value. Dependability.** When you're looking to make the most of your next project, count on Ply Gem Windows & Doors Pro Series. Our extensive product line provides you with the choices you want and the custom solutions you need. Designed with a deeper, full line frame, these windows are energy efficient, provide enhanced strength and stability and are virtually maintenance free. You'll not only enhance the view, you'll help bring a room to life.



# 200 SINGLE HUNG

plygem.com/windows-doors



## COLOR OPTIONS

Solid Vinyl Colors



Also available in Black, Bronze and Silver exterior painted colors with white interior.

Co-extruded Exterior Colors  
Geographically limited availability



## PERFORMANCE

NFRC THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
<b>WITH WARM EDGE</b>				
Clear	2.08	0.48	0.63	0.65
Low-E <sup>PS</sup>	2.86	0.35	0.46	0.56
HP	3.23	0.31	0.31	0.55
HP <sup>SC</sup>	3.23	0.31	0.22	0.44
HP2+	3.70	0.27	0.30	0.54
HP <sup>PS</sup>	3.23	0.31	0.46	0.56
HP2 <sup>MAX</sup>	4.35	0.23	0.27	0.43
HP3 <sup>MAX</sup>	4.76	0.21	0.24	0.42
<b>WITH WARM EDGE*</b>				
Clear	2.13	0.47	0.36	0.65
Low-E <sup>PS</sup>	3.03	0.33	0.46	0.56
HP	3.45	0.29	0.31	0.55
HP <sup>SC</sup>	3.45	0.29	0.22	0.44
HP2+	4.00	0.25	0.30	0.54
HP <sup>PS</sup>	3.45	0.29	0.46	0.56
HP2 <sup>MAX</sup>	4.76	0.21	0.27	0.43
HP3 <sup>MAX</sup>	5.26	0.19	0.24	0.42

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3mm glass, no grilles and IGU thickness as noted in chart.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance.

\* Laminated interior color with a co-extruded exterior color

© 2023 Ply Gem Windows & Doors, part of Cornerstone Building Brands, Inc. ALL RIGHTS RESERVED. 370614531104/REVJ/MS/IMG/0723

## STANDARD FEATURES



- Nail fin with either a 1" or 1 3/8" setback for easy and accurate installation
- Low-point, high-pressure weep system helps rain water drain efficiently from the frame
- Removable side loaded bottom sash
- Continuous weatherstripping and dual cam-action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient warm edge insulating glass for enhanced energy performance
- Corrosion-resistant fasteners and hardware for lifelong durability
- Aluminum-reinforced meeting rail for added strength and durability
- Fusion-welded corners for durability, weather-tight performance and beauty
- 3 7/8" frame depth with heavy vinyl walls for strength and stability
- Rated for light commercial application

## OPTIONS



### GLASS OPTIONS:

HP<sup>SC</sup>, HP2+, HP<sup>PS</sup>, HP2<sup>MAX</sup>, HP3<sup>MAX</sup>, (Low-E<sup>PS</sup>, Low-E2+<sup>PS</sup> and Low-E for high altitude applications), Warm Edge+, STC options, tints, obscured, laminated, tempered, single glaze

### GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulated-divided-lite (SDL) 7/8" or 1 1/4" styles; 2" accent bar

### HARDWARE OPTIONS:

AUTOLOCK-positive action lock

### FRAME OPTIONS:

Nail fin with or without stucco key or J-channel, dual wall flush fin, no fin; Insulair passive fresh air ventilation system

- Most units are rated DP40 standard
- Low-E with argon
- Optional Solar Cooling optimized Low-E with argon
- Optional triple pane, combining two panes of Low-E insulating glass with an interior glass substrate creating two chambers of argon gas fill for superior performance
- Optional Sound Control
- Optional Warm Edge+ spacer on dual pane units for enhanced performance. NOTE: Optional 1" IGU for 1" sculptured GBG and some Sound Control Glass packages. 1" sculptured GBG available with HP<sup>MAX</sup>, excluding bent grille patterns.



PART OF THE CORNERSTONE BUILDING BRANDS FAMILY | SIDING + ACCESSORIES | WINDOWS + DOORS | STONE VENEER | TRIM + MOULDINGS | FENCE + RAILING