



CSA-A440 Performance Standards

Series	Configuration	Air Leakage	Water Tightness	Wind Load
Vista	Vertical Slider	A3	B3	C4
Vista	Horizontal Slider	A3	B3	C5
Vista	Picture in Slider Frame	Fixed	B7	C3
Vista	Picture	Fixed	B7	C4
Vista	Awning	A3	B7	C3
Vista	Casement	A3	B7	C5
Vista	Fixed	Fixed	B7	C3
Vista	Direct Set	Fixed	B7	C4
Basement	Horizontal XI Slider	A3	B3	C3
Classic	Awning	A3	B7	C3
Classic	Casement	A3	B7	C5
Classic	Fixed	Fixed	B7	C3
Classic	Picture	Fixed	B7	C3
Comfort	Vertical Slider	A3	B4	C5
Comfort	Horizontal Slider	A3	B4	C4
Comfort	Picture in Slider Frame	Fixed	B7	C3
Comfort	Awning	A3	B7	C3
Comfort	Casement	A3	B7	C5
Comfort	Fixed	Fixed	B7	C3
Comfort	Direct Set	Fixed	B7	C4
Enviro	Awning	A3	B7	C3
Enviro	Casement	A3	B7	C5
Enviro	Fixed	Fixed	B7	C3
Enviro	Picture	Fixed	B7	C3
5500	Sliding Patio Door*	A3	B3	C3
Silensia	Sliding Patio Door*	A3	B2	C3
Design	Awning	A3	B7	C3
Design	Casement	A3	B7	C4
Design	Fixed	Fixed	B7	C3
Design	Direct Set	Fixed	B7	C3
Signature	Awning	A3	B4	C4
Signature	Casement	A3	B3	C3
Signature	Fixed	Fixed	B4	C3
Signature	Ext Glazed Picture	Fixed	B7	C3
Signature	Sliding Patio Door*	A3	B3	C3
Signature	Sliding Patio Door*+	A1	B3	C3

Performance rating tested to CAN/CSA A440-00 Standard.

* CAN/CGSB-821-M89 Standard

+ Based on a 6'8" door.