

PRO SERIES

W I N D O W S



200 DOUBLE HUNG



SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.

There's a clear choice when it comes to finding the style and durability you want in windows — Ply Gem Windows Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.



windows.plygem.com





200 DOUBLE HUNG



STANDARD FEATURES

- Low-maintenance cellular PVC exterior components ready to accept acrylic latex paints
- Simulated-divided-lite (SDL) options in 7/8" and 1 1/4" profiles for historically accurate appearance
- Low-maintenance cellular PVC exterior casings
- Energy-efficient Warm Edge insulating glass for enhanced energy performance
- Compression balance system for simple tilt-in cleaning of exterior glass
- Both sash tilt in and remove for safe and easy cleaning of exterior glass
- 4 9/16" jamba eliminate need for drywall work; custom jamb extensions to 8 9/16"
- Select clear wood interior ready for paint or stain to match any interior décor
- White cam-action sash locks and matching white jambliner, optional bronze tone cam-action sash locks and matching beige jambliner
- Routed finger-lifts in bottom sash rail for easy operation
- Foam-filled weatherstripping on sash for airtight performance and smooth operation



OPTIONS

GLASS OPTIONS:

Low-E, Low-E^{SC}, HP glass, HP^{SC} glass, HP2+ glass, HP2+^{SC} glass, Warm Edge+, tinted, Low-E tinted, tempered and obscure



EXTERIOR CASING:

180 Brick Mould (standard), 3 1/4" Williamsburg, 3 1/2" Flat, 5 1/2" Flat, 4 1/2" Wide Back Band, standard Sill Nose and Bull Sill Nose



GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured; 7/8" and 1 1/4" simulated-divided-lite (SDL) with shadow bar; 5/8", 7/8", 1 1/16" removable wood grilles



PRODUCT CONFIGURATION:

Twins, side lites, fixed, combinations, bays, circle heads, quarter circles, ellipticals, transoms, true radius, arches and a wide variety of architectural shapes

COLOR:

Exterior casing available in paintable white; interior available in select clear wood

200 DOUBLE HUNG³

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
5/8" Clear	2.08	0.48	0.58	0.61
5/8" Low-E	2.78	0.36	0.28	0.51
5/8" Low-E ^{SC}	2.78	0.36	0.22	0.40
5/8" Low-E2+	3.23	0.31	0.27	0.50
5/8" Low-E2+ ^{SC}	3.23	0.31	0.21	0.39
5/8" HP Glass	3.13	0.32	0.27	0.51
5/8" HP ^{SC} Glass	3.13	0.32	0.21	0.40
5/8" HP2+ Glass	3.57	0.28	0.27	0.50
5/8" HP2+ ^{SC} Glass	3.57	0.28	0.20	0.39
WITH WARM EDGE+				
5/8" Low-E	2.94	0.34	0.28	0.51
5/8" Low-E ^{SC}	2.94	0.34	0.22	0.40
5/8" Low-E2+	3.33	0.30	0.27	0.50
5/8" Low-E2+ ^{SC}	3.33	0.30	0.21	0.39
5/8" HP Glass	3.33	0.30	0.27	0.50
5/8" HP ^{SC} Glass	3.45	0.29	0.21	0.40
5/8" HP2+ Glass	3.70	0.27	0.27	0.50
5/8" HP2+ ^{SC} Glass	3.85	0.26	0.20	0.395

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3mm glass, no grilles and IGU thickness specified in the chart.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Available Low-E options.
2. Optional HP Glass packages combine Low-E options with argon gas fill for high performance.
3. Units featuring SDL require a 7/16" IGU. See page 18 of the Pro Series Brochure –Wood/Composite for thermal performance data.