

BUILDER SERIES

W I N D O W S



4720 SERIES SLIDING WINDOW



**MORE VALUE. MORE PERFORMANCE.
MORE SOLUTIONS.**

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy-efficient and offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.

www.plygemwindows.com



4720 SERIES SLIDING WINDOW



SLIDING WINDOW SELECTION GUIDE

SERIES	NAIL FIN SETBACK	SASH TYPE	BALANCE TYPE	HIGH WIND ZONE	FLORIDA APPROVED	CONSTRUCTION TYPE			
						WOOD SIDING	BRICK	BLOCK	EIFS
4720F	1 ³ / ₈ "	SIDE LOAD	BLOCK & TACKLE	●	●	●	●		●
4720FL	FLANGE	SIDE LOAD	BLOCK & TACKLE	●	●			●	

THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WARM EDGE				
3/4" Clear	1.43	0.70	0.65	0.66
3/4" Low-E	1.79	0.56	0.31	0.56
3/4" Low-E ^{SC}	1.79	0.56	0.24	0.44
3/4" HP Glass	1.92	0.52	0.31	0.56
3/4" HP ^{SC} Glass	1.92	0.52	0.24	0.44

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

STANDARD FEATURES

- Virtually maintenance-free extruded aluminum construction with electrostatically applied finish
- Removable sash
- Sleek profile provides larger viewing area
- Interior glazing allows for easier glass replacement
- Energy-efficient Warm Edge insulating glass
- 2⁷/₁₆" frame depth
- Structural meeting rail provides rigid stability and allows for a tighter, weather-resistant unit
- Push rail located at meeting rail
- Integral nailing fin (shown) or flange for simple installation



OPTIONS

GLASS OPTIONS:

Low-E, Low-E^{SC}, HP, HP^{SC}, obscure and tempered

GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in 5/8" and 3/4" flat

PRODUCT CONFIGURATION:

Two different picture configurations (1/4"-1/2"-1/4" or 1/2"-1/2"-1/2")

COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Available Low-E option.
2. Optional Low-E^{SC} features Solar Cooling optimized Low-E for warmer climates.
3. Optional HP Glass combines Low-E with argon gas fill for high performance.
4. Optional HP^{SC} Glass combines Solar Cooling optimized Low-E with argon gas fill for high performance for warmer climate zones.

5. Meets Florida building codes for certain zones. Consult your local codes for specific requirements.