

M W
PRO SERIES
W I N D O W S



200 CASEMENT & AWNING



SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.

There's a clear choice when it comes to finding the style and durability you want in windows – Ply Gem Windows MW Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.



200 CASEMENT & AWNING



STANDARD FEATURES

- Low-maintenance cellular PVC exterior components ready to accept acrylic latex paints
- Simulated-divided-lite (SDL) options in 7/8" and 1 1/4" profiles for historically accurate appearance
- Low-maintenance cellular PVC exterior brickmould
- Energy-efficient warm edge insulating glass for enhanced energy performance
- Smooth-functioning operating hardware, concealed for a clean appearance and allowing sash to open beyond a full 90°
- 4 9/16" jambs eliminate need for drywall work; custom jamb extensions to 8 9/16"
- Select clear wood interior ready for paint or stain to match any interior décor
- Concealed multi-point locking system, enhancing weather performance and security
- Leaf weatherstripping on sash and bulb weatherstripping on frame for air-tight performance and smooth operation



OPTIONS

GLASS OPTIONS:

Low-E, HP (Low-E/argon), tinted, Low-E tinted, tempered and obscure

EXTERIOR CASING:

180 Brick Mould (standard), 3 1/4" Williamsburg, 3 1/2" Flat, 4 1/2" Wide Back Band, standard Sill Nose, Bull Sill Nose

GRILLE OPTIONS:

Grilles-between-the-glass (GBG) in 5/8" and 7/8" flat, 5/8" sculptured and 1" contoured styles; 7/8" and 1 1/4" simulated-divided-lite (SDL) with shadow bar; removable 7/8" or 1 1/16" wood grilles

PRODUCT CONFIGURATION:

Twins, side lites, fixed, combinations, bays & bows, circle heads, quarter circles, ellipticals, transoms, true radius, arches and a wide variety of architectural shapes

COLOR OPTIONS:

Exterior casing available in paintable white; interior available in select clear wood



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Value	SHGC	VT
3/4" Clear	2.22	0.45	0.53	0.56
3/4" Low-E	3.03	0.33	0.25	0.47
HP Glass ²	3.33	0.30	0.25	0.47

All units tested in accordance with ASTM standards; rated in accordance with International Residential Code; and witnessed by an independent AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.



R VALUE: Restrictive ambient air flow; U VALUE: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Available option.

2. HP glass option combines Low-E with argon gas fill for high performance.

