

PRO SERIES

W I N D O W S



CLASSIC DOUBLE HUNG



SUPERIOR PERFORMANCE. ELEGANT CRAFTSMANSHIP.

There's a clear choice when it comes to finding the style and durability you want in windows — Ply Gem Windows Pro Series. Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life. You get great looks and quality without compromise.

windows.plygem.com





CLASSIC DOUBLE HUNG



STANDARD FEATURES

- Classic brickmould profile provides an authentic sculptured appearance that matches traditional exterior millwork
- Interior and exterior accessory grooves allow for easy accessory application
- Both sash tilt in and remove for safe and easy cleaning of exterior glass
- Weather-tight dual action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient WarmEdge insulating glass for enhanced energy performance
- Low-profile sill nosing resembles a traditional wood window
- Integral nail fin with fusion-welded corners for simple and accurate installation
- Maintenance-free multi-chamber PVC construction with fusion-welded corners for durability, weather-tight performance and beauty
- Robust interlock satisfies forced entry requirements and improves structural performance
- Integral $1\frac{1}{16}$ " siding pocket with undersill trim leg allows for simple and secure siding installation



OPTIONS

GLASS OPTIONS:

Low-E, Low-E^{SC}, Low-E2+, Low-E2+^{SC}, LE^{PS}, LE2+^{PS}, HP, HP^{SC}, HP2+, HP2+^{SC}, HP^{PS}, HP2+^{PS} WarmEdge+, tinted, tempered, obscure, and spandrel glass

GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat $\frac{5}{8}$ " and $\frac{7}{8}$ ", sculptured $\frac{5}{8}$ " and 1" styles, $\frac{7}{8}$ " and 1 $\frac{1}{4}$ " simulated divided lites (SDL)

EXTENSION JAMBS:

Custom to 9 $\frac{1}{8}$ " in primed or natural wood, and cellular PVC

PRODUCT CONFIGURATION:

Singles, twins, triples, side lites, fixed, combinations, 30° and 45° bays and a wide variety of architectural shapes

COLOR OPTIONS:



DOUBLE HUNG THERMAL PERFORMANCE

For comparison, these are a few select configurations using 3mm glass within a 3/4" IGU and no grilles

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
LE	2.94	0.34	0.28	0.52
LE ^{SC}	2.94	0.34	0.22	0.41
HP	3.23	0.31	0.28	0.52
HP ^{PS}	3.23	0.31	0.44	0.54
HP ^{SC}	3.33	0.30	0.21	0.41
LE2+	3.45	0.29	0.27	0.51
LE2+ ^{SC}	3.45	0.29	0.21	0.40
HP2+ ^{PS}	3.57	0.28	0.43	0.54
HP2+	3.70	0.27	0.27	0.51
HP2+ ^{SC}	3.70	0.27	0.21	0.40
WITH WARM EDGE PLUS SPACER				
HP	3.33	0.30	0.28	0.52
HP ^{PS}	3.33	0.30	0.44	0.54
HP ^{SC}	3.45	0.29	0.21	0.41
HP2+ ^{PS}	3.70	0.27	0.43	0.54
HP2+	3.85	0.26	0.27	0.51
HP2+ ^{SC}	3.85	0.26	0.21	0.40

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: $\frac{3}{4}$ " IGU, 3mm glass and no grilles.

R-value: Restrictive ambient air flow; U-factor: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching.