



Home Innovation
NGBS GREEN CERTIFIED™

THIS IS TO SIGNIFY THAT THE FOLLOWING
PRODUCTS FOR RESIDENTIAL CONSTRUCTION

**PLY GEM ALUMINUM GUTTER AND DOWNSPOUT
SYSTEMS (SECTIONAL & SEAMLESS)**

MANUFACTURED BY
PLY GEM INDUSTRIES

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN
CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING
STANDARD AS DETAILED IN NGBS GREEN CERTIFIED
PRODUCT REPORT #NGBSGCP-00089.

Thomas M. Kenney, P.E. – VP Research & Engineering

October 26, 2009

Approval Date

April 30, 2019

Expiration Date

CERTIFICATE #00089

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certified Product Report #NGBSGCP-00089

Products: Ply Gem Aluminum Gutter and Downspout Systems (Sectional & Seamless)

Manufacturer: Ply Gem Industries

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2012 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2012 NGBS 602.5	Gutter/downspout/splash blocks grading carry water a minimum of 5' from perimeter foundation.	4	Product is used to carry rainwater at least 5 feet away from foundation.
2012 NGBS 604.1(1)	Building materials w/ recycled content are used for at least 2 minor components.	1-2	Points awarded for 2 products w/ recycled content. Use of another minor product with at least 75% recycled content required for 3 points.

2015 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2015 NGBS 602.5	Gutter/downspout/splash blocks grading carry water a minimum of 5' from perimeter foundation.	4	Product is used to carry rainwater at least 5 feet away from foundation.
2015 NGBS 604.1(1)	Building materials w/ recycled content are used for at least 2 minor components.	1-2	Points awarded for 2 products w/ recycled content. Use of another minor product with at least 75% recycled content required for 3 points.