

PRO SERIES

W I N D O W S

PlyGem[®]
WINDOWS & DOORS



200 SINGLE HUNG



LOOKS THAT LAST. STYLES THAT STAND OUT.

Style. Value. Dependability. When you're looking to make the most of your next project, count on Ply Gem Windows & Doors Pro Series. Our extensive product line provides you with the choices you want and the custom solutions you need. Designed with a deeper, full line frame, these windows are energy efficient, provide enhanced strength and stability and are virtually maintenance free. You'll not only enhance the view, you'll help bring a room to life.

plygem.com/windows



200 SINGLE HUNG



STANDARD FEATURES

- Nail fin with either a 1" or 1-3/8" setback for easy and accurate installation
- Low-point, high-pressure weep system helps rain water drain efficiently from the frame
- Removable side loaded bottom sash
- Continuous weatherstripping and dual cam-action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient warm edge insulating glass for enhanced energy performance
- Corrosion-resistant stainless steel screws and hardware for lifelong durability
- Aluminum-reinforced meeting rail for added strength and durability
- Maintenance-free multi-chamber PVC construction with fusion welded corners for durability, weather-tight performance and beauty
- 3-7/16" frame depth with heavy vinyl walls for strength and stability
- Rated for light commercial application



OPTIONS

GLASS OPTIONS:

HP, HP^{SC}, HP^{MAX}, Warm Edge⁺, STC options, tints, obscure, laminated, tempered, single glaze

GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8", sculptured 5/8" or 1" styles; simulated-divided-lite (SDL) 7/8" or 1-1/4" styles; 2" accent bar

HARDWARE OPTIONS:

AUTOLOCK—positive action lock

FRAME OPTIONS:

Nail fin with or without stucco key or J-channel, dual wall flush fin, no fin; Insulair passive fresh air ventilation system

COLOR OPTIONS:



CO-EXTRUDED EXTERIOR COLORS

Geographically limited availability



Black, Bronze and Silver exterior painted colors with white interior available.



THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
3/4" Low-E ^{SC}	2.86	0.35	0.22	0.43
3/4" HP	3.13	0.32	0.29	0.54
3/4" HP ^{SC}	3.13	0.32	0.22	0.43
1" HP ^{MAX}	4.17	0.24	0.25	0.42
WITH WARM EDGE⁺				
3/4" HP	3.33	0.30	0.29	0.54
3/4" HP ^{SC}	3.33	0.30	0.22	0.43

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3mm glass, no grilles and IGU thickness as noted in chart.



R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors are reproduced as accurately as printer technology allows. Please see your authorized Ply Gem Windows representative for actual samples.

1. Most units are rated DP40 standard 2. Low-E with argon 3. Optional Solar Cooling optimized Low-E with argon. 4. Optional triple pane, combining two panes of Low-E insulating glass with an interior glass substrate creating two chambers of argon gas fill for superior performance 5. Optional Sound Control 6. Optional Warm Edge+ spacer on dual pane units for enhanced performance. NOTE: Optional 1" IGU for 1" sculptured GBG and some Sound Control Glass packages. 1" sculptured GBG available with HP^{MAX}, excluding bent grille patterns.

