




Home Innovation
NGBS GREEN CERTIFIED™

THIS IS TO SIGNIFY THAT THE FOLLOWING
PRODUCTS FOR RESIDENTIAL CONSTRUCTION

PLY GEM VINYL RAILING

MANUFACTURED BY
PLY GEM INDUSTRIES

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN
CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING
STANDARD AS DETAILED IN NGBS GREEN CERTIFIED
PRODUCT REPORT #NGBSGCP-00132.



Thomas M. Kenney, P.E. – VP Research & Engineering

April 26, 2010

Approval Date

April 30, 2019

Expiration Date

CERTIFICATE #00132

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



NGBS Green Certified Product Report #NGBSGCP-00132

Products: Ply Gem Vinyl Railing

Manufacturer: Ply Gem Industries

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

| 2012 NATIONAL GREEN BUILDING STANDARD | | | |
|---------------------------------------|---|----------------------------|--|
| PRACTICE # | PRACTICE DESCRIPTION | POTENTIAL POINTS AVAILABLE | ADDITIONAL CONDITIONS OF USE TO AWARD POINTS |
| 2012 NGBS 602.1.6 | Termite-resistant materials are used in portions of the building. | 2-6 | To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites. |

| 2015 NATIONAL GREEN BUILDING STANDARD | | | |
|---------------------------------------|---|----------------------------|--|
| PRACTICE # | PRACTICE DESCRIPTION | POTENTIAL POINTS AVAILABLE | ADDITIONAL CONDITIONS OF USE TO AWARD POINTS |
| 2015 NGBS 602.1.6 | Termite-resistant materials are used in portions of the building. . . | 2-6 | To earn 2 points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall clading, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use in all of the foundation, floor, and structural wall, wall clading, and exterior deck components in areas of very heavy termites. |