

# BUILDER SERIES

W I N D O W S



## 4720 SERIES SLIDING WINDOW



**MORE VALUE. MORE PERFORMANCE.  
MORE SOLUTIONS.**

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. It's energy-efficient and offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time. Plus, with our service and support you'll be able to get the job done the right way on time and on budget.



# 4720 SERIES SLIDING WINDOW



## SLIDING WINDOW SELECTION GUIDE

SERIES	NAIL FIN SETBACK	HIGH WIND ZONE	FLORIDA APPROVED	CONSTRUCTION TYPE			
				WOOD SIDING	BRICK	BLOCK	EIFIS
4720F	1 <sup>3</sup> / <sub>8</sub> "	●	●	●	●		●
4720FL	FLANGE	●	●			●	

## THERMAL PERFORMANCE

	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
<b>WARM EDGE</b>				
3/4" Clear	1.45	0.69	0.65	0.66
3/4" Low-E	1.85	0.54	0.31	0.56
3/4" Low-E <sup>SC</sup>	1.85	0.54	0.24	0.44
3/4" HP Glass	1.96	0.51	0.31	0.56
3/4" HP <sup>SC</sup> Glass	2.00	0.50	0.24	0.44

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

## STANDARD FEATURES

- Virtually maintenance-free extruded aluminum construction with electrostatically applied finish
- Removable sash
- Sleek profile provides larger viewing area
- Interior glazing allows for easier glass replacement
- Energy-efficient Warm Edge insulating glass
- 2<sup>7</sup>/<sub>16</sub>" frame depth
- Structural meeting rail provides rigid stability and allows for a tighter, weather-resistant unit
- Push rail located at meeting rail
- Integral nailing fin (shown) or flange for simple installation



## OPTIONS

### GLASS OPTIONS:

Low-E, Low-E<sup>SC</sup>, HP, HP<sup>SC</sup>, obscure and tempered

### GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in 5/8", 3/4" flat and 1<sup>3</sup>/<sub>16</sub>" simulated divided lite (SDL)

### PRODUCT CONFIGURATION:

Two different picture configurations (1/4–1/2–1/4 or 1/3–1/3–1/3)

### COLOR OPTIONS:



NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

1. Available Low-E option.
2. Optional HP Glass combines Low-E with argon gas fill for high performance.
3. Meets Florida building codes for certain zones. Consult your local codes for specific requirements.

