



## 3710 SERIES SINGLE HUNG

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. **It's energy efficient, offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time.** Plus, with our service and support you'll be able to get the job done the right way on time and on budget.



# 3710 SERIES SINGLE HUNG

plygem.com/windows



## COLOR OPTIONS:



## PERFORMANCE:

3710N <sup>3</sup> THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
5/8" Clear	1.52	0.66	0.65	0.68
5/8" Low-E	1.92	0.52	0.32	0.57
5/8" Low-E <sup>SC</sup>	1.92	0.52	0.25	0.45
5/8" HP Glass	2.08	0.48	0.32	0.58
5/8" HP <sup>SC</sup> Glass	2.08	0.48	0.25	0.46
3710F <sup>4</sup> THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
5/8" Clear	1.49	0.67	0.65	0.68
5/8" Low-E	1.89	0.53	0.32	0.57
5/8" Low-E <sup>SC</sup>	1.89	0.53	0.25	0.45
5/8" HP Glass	2.00	0.50	0.32	0.58
5/8" HP <sup>SC</sup> Glass	2.04	0.49	0.25	0.46

3. 3710N units feature a 2" frame depth.

4. 3710F units feature a 2 7/16" frame depth.

All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: 5/8" IGU, 3mm glass, no grilles.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

© 2023 Ply Gem Windows & Doors, part of Cornerstone Building Brands, Inc. ALL RIGHTS RESERVED. 375101101118/REV/FMS/CG/0323

## STANDARD FEATURES



- Virtually maintenance-free extruded aluminum construction with electrostatically applied finish.
- Sloped sill allows for proper water drainage to the exterior
- Sleek profile provides larger viewing area
- Interior glazing allows for easier glass replacement
- Side loading removable bottom sash
- Block and tackle balance for smooth operation
- Energy-efficient warm edge insulating glass for enhanced performance
- 2" or 2 7/16" frame depth (see chart below)
- Structural meeting rail provides rigid stability and allows for a tighter, weather-resistant unit
- Dual lift rails on bottom sash for easy operation
- Integral nailing fin for simple installation

## OPTIONS



### GLASS OPTIONS:

Low-E, Low-E<sup>SC</sup>, HP, HP<sup>SC</sup>, obscure and tempered



### GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in 5/8" and 3/4" flat

### PRODUCT CONFIGURATION:

Twins, triples, combinations, fixed and a wide selection of architectural shapes

### HARDWARE OPTION:

Safety vent latch to meet ASTM F2090-2008 requirements

SINGLE HUNG SELECTION GUIDE						
Series	Frame Depth	Nail Fin Setback	CONSTRUCTION TYPE			
			Wood Siding	Brick	3 Coat Stucco	EIFIS
3710N	2"	1 3/8"			•	•
3710F	2 7/16"	1 3/8"	•	•	•	•

1. Available Low-E option.

2. Optional HP Glass combines Low-E with argon gas fill for high performance.



PART OF THE CORNERSTONE BUILDING BRANDS FAMILY | SIDING + ACCESSORIES | WINDOWS + DOORS | STONE VENEER | TRIM + MOULDINGS | FENCE + RAILING