



3724 SERIES SLIDING WINDOW

If you're looking for a window that delivers the best possible performance at the best possible value, look no further than Ply Gem Windows Builder Series. **It's energy-efficient, offers a variety of material choices, most of which are virtually maintenance free and can withstand the toughest tests, including the test of time.** Plus, with our service and support you'll be able to get the job done the right way on time and on budget.



3724 SERIES SLIDING WINDOW

plygem.com/windows



COLOR OPTIONS:



PERFORMANCE:

THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
5/8" Clear	1.43	0.70	0.66	0.67
5/8" Low-E	1.82	0.55	0.32	0.57
5/8" Low-E ^{SC}	1.82	0.55	0.25	0.45
5/8" HP Glass	2.00	0.50	0.32	0.57
5/8" HP ^{SC} Glass	2.00	0.50	0.25	0.45

SLIDING WINDOW SELECTION GUIDE							
Series	Nail Fin Setback	High Wind Zone	Florida Approved	CONSTRUCTION TYPE			
				Wood Siding	Brick	Block	EIFIS
3724N	1 3/8"	•	14250	•	•		•
3724F	Flange	•	14250			•	

All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: 5/8" IGU, 3mm glass, no grilles.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

STANDARD FEATURES



- Virtually maintenance-free extruded aluminum construction with electrostatically applied finish
- Removable sash for simple cleaning
- Sleek profile provides larger viewing area
- Interior glazing allows for easier glass replacement
- Energy-efficient Warm Edge insulating glass
- 2" frame depth with optional nail fin setback
- Structural meeting rail provides rigid stability and allows for a tighter, weather-resistant unit
- Push rail conveniently located at meeting rail
- Integral nailing fin (shown) or flange for simple installation

OPTIONS



GLASS OPTIONS:

Low-E, Low-E^{SC}, HP, HP^{SC}, obscure and tempered



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in 5/8" and 3/4" flat



PRODUCT CONFIGURATION:

Two different picture configurations (1/4-1/2-1/4 or 1/3-1/3-1/3)

1. Optional Low-E and Low-E^{SC} (solar cooling) glass packages.
2. Optional HP and HP^{SC} (solar cooling) glass packages combine Low-E glass options with argon gas fill for high performance.
3. 3724 meets Florida building codes for certain zones. Consult your local codes for specific requirements.

