



## CLASSIC CASEMENT & AWNING

There's a clear choice when it comes to finding the style and durability you want in windows — Ply Gem Windows Pro Series. **Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life.** You get great looks and quality without compromise.



## COLOR OPTIONS:



## PERFORMANCE:

CASEMENT THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
<b>WITH WARM EDGE</b>				
LE	3.13	0.32	0.25	0.46
LE <sup>SC</sup>	3.33	0.3	0.19	0.36
LE2+	3.57	0.28	0.24	0.45
LE2+ <sup>SC</sup>	3.57	0.28	0.19	0.35
HP	3.45	0.29	0.25	0.46
HP <sup>SC</sup>	3.57	0.28	0.19	0.36
HP2+	3.85	0.26	0.24	0.45
HP2+ <sup>SC</sup>	4.00	0.25	0.18	0.35
<b>WITH WARM EDGE+</b>				
HP	3.57	0.28	0.25	0.46
HP <sup>SC</sup>	3.70	0.27	0.19	0.36
HP2+	4.00	0.25	0.24	0.45
HP2+ <sup>SC</sup>	4.00	0.25	0.18	0.35

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

## STANDARD FEATURES



- Sash opens 90° for ventilation and easy cleaning
- Accessory grooves allow for easy accessory application
- Single-handle multi-point locking system with stainless steel lockbar for all standard sizes
- Weather-tight sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient WarmEdge insulating glass for enhanced energy performance
- Split-arm gear operator for call sizes up to 3050; dual-arm gear operator on larger units
- Integral nailing fin with welded corners for simple and accurate installation
- Maintenance-free multi-chamber PVC construction with fusion welded corners for durability, weather-tight performance and beauty
- Adjustable hinge with stainless steel hinge track

## OPTIONS



### GLASS OPTIONS:

Low-E, Low-E<sup>SC</sup>, Low-E2+, Low-E2+<sup>SC</sup>, HP, HP<sup>SC</sup>, HP2+, HP2+<sup>SC</sup>, Warm Edge+, tinted, tempered, obscure, and spandrel glass



### GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8" and 7/8", sculptured 5/8" and 1" styles, 7/8" and 1 1/4" simulated divided lites (SDL)



### ACCESSORIES:

Snap-on flat casing, coastal hardware, 3 1/2" flat casing and expanded access hardware



### EXTENSION JAMBS:

Custom to 9/8" in primed or natural "clear" wood, and 3/4" receiver



### PRODUCT CONFIGURATION:

Singles, twins, triples, side lites, fixed, combinations, 30° and 45° bays & bows and a wide variety of architectural shapes

