



CLASSIC DOUBLE HUNG

There's a clear choice when it comes to finding the style and durability you want in windows — Ply Gem Windows Pro Series. **Our distinct product offerings provide you with the selection and craftsmanship you need to bring your next project to life.** You get great looks and quality without compromise.



CLASSIC DOUBLE HUNG

plygem.com/windows



COLOR OPTIONS:



PERFORMANCE:

DOUBLE HUNG THERMAL PERFORMANCE				
	R Value	NFRC CERTIFIED		
		U Factor	SHGC	VT
WITH WARM EDGE				
LE	2.94	0.34	0.28	0.52
LE ^{SC}	2.94	0.34	0.22	0.41
LE ^{PS}	2.94	0.34	0.43	0.54
HP	3.23	0.31	0.28	0.52
HP ^{PS}	3.23	0.31	0.44	0.54
HP ^{SC}	3.33	0.30	0.21	0.41
LE2+	3.45	0.29	0.27	0.51
LE2+ ^{SC}	3.45	0.29	0.21	0.40
HP2+	3.70	0.27	0.27	0.51
HP2+ ^{SC}	3.70	0.27	0.21	0.40
WITH WARM EDGE+				
HP	3.33	0.30	0.28	0.52
HP ^{PS}	3.33	0.30	0.44	0.54
HP ^{SC}	3.45	0.29	0.21	0.41
HP2+	3.85	0.26	0.27	0.51
HP2+ ^{SC}	3.85	0.26	0.21	0.40

For comparison, these are a few select configurations using 3mm glass within a 3/4" IGU and no grilles.

All units are NAMI certified and rated in accordance with NFRC 100/200 standards by an AAMA accredited lab. Performance values reflect the performance of units tested with the following configuration: 3/4" IGU, 3mm glass and no grilles.

R-value: Restrictive ambient air flow; U-factor: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so.

STANDARD FEATURES



- Classic brickmould profile provides an authentic sculptured appearance that matches traditional exterior millwork
- Interior and exterior accessory grooves allow for easy accessory application
- Both sash tilt in and remove for safe and easy cleaning of exterior glass
- Weather-tight dual action sash lock provides security while sealing out the weather and sealing in your comfort
- Energy-efficient WarmEdge insulating glass for enhanced energy performance
- Low-profile sill nosing resembles a traditional wood window
- Integral nail fin with fusion-welded corners for simple and accurate installation
- Maintenance-free multi-chamber PVC construction with fusion-welded corners for durability, weather-tight performance and beauty
- Robust interlock satisfies forced entry requirements and improves structural performance
- Integral 1/16" siding pocket with undersill trim leg allows for simple and secure siding installation

OPTIONS



GLASS OPTIONS:

Low-E, Low-E^{SC}, Low-E2+, Low-E2+^{SC}, LE^{PS}, HP, HP^{SC}, HP2+, HP2+^{SC}, HP^{PS}, WarmEdge+, tinted, tempered, obscure, and spandrel glass



GRILLE OPTIONS:

Color-coordinated grilles-between-the-glass (GBG) in flat 5/8" and 3/8", sculptured 5/8" and 1" styles, 3/8" and 1 1/4" simulated divided lites (SDL)



EXTENSION JAMBS:

Custom to 9 1/8" in primed or natural wood, and cellular PVC

PRODUCT CONFIGURATION:

Singles, twins, triples, side lites, fixed, combinations, 30° and 45° bays and a wide variety of architectural shapes

