



**Home Innovation**  
NGBS GREEN CERTIFIED™

THIS IS TO SIGNIFY THAT THE FOLLOWING  
PRODUCTS FOR RESIDENTIAL CONSTRUCTION

**PLY GEM PREMIUM VINYL SIDING**

MANUFACTURED BY  
**PLY GEM INDUSTRIES**

HAVE BEEN CERTIFIED FOR POINTS TOWARD NGBS GREEN  
CERTIFICATION TO THE ICC 700 NATIONAL GREEN BUILDING  
STANDARD AS DETAILED IN NGBS GREEN CERTIFIED  
PRODUCT REPORT #NGBSGCP-00085.

Thomas M. Kenney, P.E. – VP Research & Engineering

October 26, 2009

Approval Date

April 30, 2019

Expiration Date

**CERTIFICATE #00085**

This certificate is not a representation, warranty, or guarantee of product performance or certification of code compliance. For details of the product warranty, consult the product manufacturer.



**NGBS Green Certified Product Report #NGBSGCP-00085**

**Products:** Ply Gem Premium Vinyl Siding

**Manufacturer:** Ply Gem Industries

The product(s) shown on this report have been independently verified as eligible products for use in achieving points toward project certification under ICC-700 National Green Building Standard. Home Innovation Research Labs authorizes accredited verifiers to award points toward certification without additional documentation when the product(s) is used as noted below.

2012 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS
2012 NGBS 601.7	Building materials/assemblies do not require additional site applied material for finishing. 12 points max. awarded.	2-5	For 5 points, 90% or more of the installed exterior wall coverings must be this product. For 2 points, 50-90% of the installed exterior wall coverings must be this product.
2012 NGBS 602.1.6	Termite-resistant materials are used in portions of the building. . .	2-6	To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in conjunction with other termite resistant materials for the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use with other termite resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.

2015 NATIONAL GREEN BUILDING STANDARD			
PRACTICE #	PRACTICE DESCRIPTION	POTENTIAL POINTS AVAILABLE	ADDITIONAL CONDITIONS OF USE TO AWARD POINTS

<p>2015 NGBS 601.7</p>	<p>Building materials/assemblies do not require additional site applied material for finishing. 12 points max. awarded.</p>	<p>2-5</p>	<p>For 5 points, 90% or more of the installed exterior wall coverings must be this product. For 2 points, 50-90% of the installed exterior wall coverings must be this product.</p>
<p>2015 NGBS 602.1.6</p>	<p>Termite-resistant materials are used in portions of the building. . .</p>	<p>2-6</p>	<p>To earn two points, product is used in conjunction with other termite resistant materials for the first 2 feet of all the foundation, floor, and structural wall, wall cladding, and exterior deck components in zones with slight to moderate termite infestation. 4 points are awarded when used in conjunction with other termite resistant materials for the first 3 feet in moderate to heavy termite zones, and 6 points are awarded for use with other termite resistant materials for all of the foundation, floor, and structural wall, wall cladding, and exterior deck components in areas of very heavy termites.</p>